SEPREMIUM 3.5

Oil/water separator for compressor capacities up to 3,5 m^3/min.

PRODUCT FEATURES

The SEPREMIUM range of oil/water separators separates oil from condensate, generated by compressed air systems. The SEPREMIUM achieves efficient separation of oil from condensate by means of directing the condensate through various filtration stages.

As condensate flows in to the SEPREMIUM, the oil is filtered out through various filtration elements.

The oil adsorbing elements combine various types of adsorption technologies to achieve less than 10 ppm oil residue values at the output stage.

The SEPREMIUM 3.5 is designed to be versatile and compact.

The elements are lightweight and servicing is a quick and above all clean process.

COMMERCIAL BENEFITS

- Separation of all types of compressor lubricants
- Compact design and small footprint, offering:
  - easy handling
  - flexible installation benefits
- Clothing kit included
- Competitive pricing levels
- Consult JORC for private labelling options

TECHNICAL ADVANTAGES

- High performance filtration materials applied
- Simple, fast and clean installation and maintenance procedure
- Successful separation of mineral oil, synthetic lubricants and stabile emulsions
- Test bottle included for routine output testing schedules
- Fixing bracket for wall mounting optionally available
- Brass threaded inlet/outlet, ensuring a secure installation (hose barbs are included)

THE COMPRESSED AIR CONDENSATE MANAGEMENT SPECIALIST

THE COMPRESSED AIR CONDENSATE MANAGEMENT SPECIALIST

SEPREMIUM 3.5

Oil/water separator for compressor capacities up to 3,5 m³/min.

DIMENSIONS

Replacement service pack

Routine testing feature incl.

Fixing bracket available

TECHNICAL SPECIFICATIONS

Max. compressor capacity	3,5 m³/min.
Max. oil adsorption in the elements	4 litres
Brass inlet connection	1/2" (hose barb included)
Brass outlet connection	1/2" (hose barb included)
TEST kit	Yes
Target output value	<10 ppm
Housing material	PE
Total recyclable	Yes
Housing colour	Black
Lid colour	Grey

SEPARATION OF:

Mineral lubricants	Yes
Synthetic lubricants	Yes
Stabile condensate emulsions*	Yes
Ultra-Coolant*, Sigma Mol*	Yes
Roto-Inject*	Yes

**Ultra-Coolant, Sigma Mol and Roto-Inject are registred trade names of producers of compressor lubricants.*

The SEPREMIUM 3.5 can be applied as a stand-alone item or as part of an integrated package of the compressor system. The compact size allows for easy installation inside compressor packages.

JORC is NEN - EN - ISO 9001:2015 certified

Information provided herewith is believed to be accurate and reliable. However, no responsibility is assumed for its use or for any infringement of patents or rights of others, which may result from its use. In addition, JORC reserves the right to revise information without notice and without incurring any obligation.

At www.nordicfiltration.com you will find a wide selection of filtration products ready for you to order.

Nordic Filtration offers a wide selection of filtration products for water treatment. We have stock in Denmark from where we distribute all of our products to Scandinavia and the the rest of the world.

You can buy our products on local websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our website (www.nordicfiltration.com).

We can adapt all of our filtration products to your needs, and we offer visits from our consultants in order to find the right solution for you.

Filter-Online & Nordic Filtration ApS
Glasvænget 6
5492 Vissenbjerg
Denmark

+45 72 25 10 00
info@nordicfiltration.com
www.nordicfiltration.com