

FILTER ELEMENT – Atlas Copco Gen 2

Alternative filter elements for Atlas Copco 2. Generation

Series: DD, PD, QD



DESCRIPTION

These filter elements have been developed for high efficient removal of solid particles, oil aerosols, water, hydrocarbons, vapours and odours from compressed air.

FILTER ELEMENT RATING ACCORDING TO ISO 8573-1

Filtration grade	Solid particles class	Water class	Oil class
DD/XM	2	/	2
PD/XS	1	/	1
QD/A	1*	/	0/1

Validated according to ISO12500-1, ISO12500-2 and ISO12500-3

* Valid if "XS" filter cartridge is installed upstream

TECHNICAL SPECIFICATION

	DD/XM ⁽⁶⁾	PD/XS ⁽⁶⁾	QD/A ⁽⁶⁾
Operating temperature	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 45 °C/ 35 - 113 °F
Operating pressure	0 - 16 barg/ 0 - 232 psi	0 - 16 barg/ 0 - 232 psi	0 - 16 barg/ 0 - 232 psi
Differential pressure (dry)	50 mbar/ 0,725 psi	80 mbar/ 1,160 psi	60 mbar/ 0,870 psi
Differential pressure (wet)	120 mbar/ 1,740 psi	190 mbar/ 2,756 psi	/
Particle retention (nominal)	99,9999% (0,1 µm)	99,9999% (0,01 µm)	/
Particle retention rate ISO ⁽³⁾	99,98 %	99,9994 %	/
Residual oil content ⁽⁴⁾	< 0,1mg/m ³	< 0,01mg/m ³	< 0,005mg/m ³
Flow Direction	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE
Capacity (ISO12500-2) ⁽⁵⁾	/	/	20 min

⁽³⁾Tested according to ISO12500-3, 1bar(a), nominal flow, 06050 M, S, MPPS-(0,3µm)

⁽⁴⁾Tested according to ISO12500-1, 06050 M, S Oil aerosol viscosity 32mm²/s, inlet concentration 10mg/m³

⁽⁵⁾Tested according to ISO12500-2, 06050 A, tested with n-Hexane, test concentration 100mg/kg, 80% Saturation

⁽⁶⁾Cross reference Omega Air – Atlas Copco filtration grades: XM=DD/XM, XS=PD/XS, A=QD/A

CORRECTION FACTORS

To calculate the correct capacity of a given filter based on actual operating conditions, multiply the nominal flow capacity by the appropriate correction factor(s). CORRECTED CAPACITY = NOMINAL FLOW CAPACITY x C_{OP}

OPERATING PRESSURE

[bar]	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
[psi]	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232
C _{OP}	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13

MATERIALS

	DD/XM	PD/XS	QD/A
Filter media	Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers
Protection media	Polyester fleece	Polyester fleece	Polyester fleece
Drainage media	Polyester needle felt	Polyester needle felt	/
Adsorption media	/	/	Activated carbon granulate
Support (inner-outer)	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301
Bonding	Polyurethane	Polyurethane	Polyurethane
Endcaps	PA6 with 30% glass fibers or aluminium	PA6 with 30% glass fibers or aluminium	PA6 with 30% glass fibers or aluminium
Sealing	NBR	NBR	NBR

SIZES

Model* (Plastic endcaps)	Model* (Aluminium endcaps)	Diameter [mm]	Height [mm]	Flow Capacity [Nm ³ /h]	Flow Capacity [scfm]	Fits into filter housing
OAC 9	OAC 9	46	55,5	32,4	19	9 G
OAC 17	OAC 17	46	90,5	61,2	36	17 G
OAC 32	OAC 32	46	146	115,2	68	32 G
OAC 44	OAC 44	61	155	158,4	93	44 G
OAC 60	OAC 60	61	195	216	127	60 G
OAC 120	OAC 120	86	288	432	254	120 G
OAC 150	OAC 150	86	323	540	318	150 G
OAC 175	OAC 175	86	367,5	630	371	175 G
/	OAC 260/280	101,5	420	1008	593	280 G
OAC 390	OAC 390	120	509	1404	826	390 G
OAC 520	OAC 520	120	679	1872	1102	520 G
/	OAC 520F	120	683	1872	1102	520 F
/	OAC 780F	88	584	2808	1653	780 F
/	OAC 850F	87,5	622	3780	2225	850 F

*Filter cartridge names consist of cartridge size and filtration grade. Place filtration grade designation after filter size (e.g. OAC 9 DD/XM). There is an option for **aluminum endcaps** (e.g. OAC 9 DD/XM AI).

MAINTENANCE

DD/XM, PD/XS - Replace filter element at least once per year or when pressure drop reaches 350mbar

QD/A - Replace filter element at least every 6 months



Strength

- We export to almost 100 countries.
- We have more than 2000 global customers.
- We can provide a total filtration solution.

- Filter-Online & Nordic Filtration offers a wide selection of filtration products for Domestic and Industrial Application.

- You can buy our products on our websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our websites:

www.filter-online.com for Domestic Products

nordicfiltration.com for Industrial Products

We distribute many of our products from our stock in Denmark. Some products are shipped from remote stock.



Filter-Online & Nordic Filtration ApS
Glasvænget 6
5492 Vissenbjerg
Denmark

Filter-Online
+45 70 40 42 22
info@filter-online.com
www.filter-online.com

Nordic Filtration
+45 72 25 10 00
info@nordicfiltration.com
nordicfiltration.com