



# FILTER ELEMENT – BEKO

Alternative filter elements for Beko - Clearpoint

Series: Clearpoint 3eco



## DESCRIPTION

These filter elements have been developed for high efficient removal of solid particles, oil aerosols, water, hydrocarbons, vapours and odours from compressed air.

## FILTER ELEMENT RATING ACCORDING TO ISO 8573-1

Filtration grade	Solid particles class	Water class	Oil class
G	6	/	/
F	2	/	2
S	1	/	1
A	1*	/	0/1

Validated according to ISO12500-1, ISO12500-2 and ISO12500-3

## TECHNICAL SPECIFICATION

	G	F	S	A
Operating temperature	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 45 °C/ 35 - 113 °F
Operating pressure	0 - 16 barg/ 0 - 232 psi			
Differential pressure (dry)	10 mbar/ 0,145 psi	50 mbar/ 0,725 psi	80 mbar/ 1,160 psi	60 mbar/ 0,870 psi
Differential pressure (wet)	20 mbar/ 0,290 psi	120 mbar/ 1,740 psi	190 mbar/ 2,756 psi	/
Particle retention (nominal)	99,99% (3 µm)	99,9999% (0,1 µm)	99,9999% (0,01 µm)	/
Particle retention rate ISO <sup>(3)</sup>	95 %	99,98 %	99,9994 %	/
Residual oil content <sup>(4)</sup>	/	< 0,1mg/m <sup>3</sup>	< 0,01mg/m <sup>3</sup>	< 0,005mg/m <sup>3</sup>
Flow Direction	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE
Capacity (ISO12500-2) <sup>(5)</sup>	/	/	/	20 min

<sup>(3)</sup>Tested according to ISO12500-3, 1bar(a), nominal flow, 06050 P, MPPS-(5µm) ; 06050 M, S, MPPS-(0,3µm)

<sup>(4)</sup>Tested according to ISO12500-1, 06050 M, S Oil aerosol viscosity 32mm<sup>2</sup>/s, inlet concentration 10mg/m<sup>3</sup>

<sup>(5)</sup>Tested according to ISO12500-2, 06050 A, tested with n-Hexane, test concentration 100mg/kg, 80% Saturation

## CORRECTION FACTORS

To calculate the correct capacity of a given filter based on actual operating conditions, multiply the nominal flow capacity by the appropriate correction factor(s). CORRECTED CAPACITY = NOMINAL FLOW CAPACITY x C<sub>OP</sub>

### OPERATING PRESSURE

[bar]	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
[psi]	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232
C <sub>OP</sub>	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13



## MATERIALS

	G	F	S	A
Filter media	Acrylic fibers, cellulose	Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers
Protection media	Polyester fleece	Polyester fleece	Polyester fleece	Polyester fleece
Drainage media	/	Polyester based polyurethane	Polyester based polyurethane	/
Adsorption media	/	/	/	Activated carbon granulate
Support (inner-outer)	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301
Bonding	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Endcaps	PA6 with 30% glass fibers <sup>(7)</sup>			
Sealing	NBR	NBR	NBR	NBR

<sup>(7)</sup>Exception: BK 88 has aluminium endcaps

## SIZES

Model*	Diameter [mm]	Height [mm]	Flow Capacity [Nm <sup>3</sup> /h]	Flow Capacity [scfm]	Fits into filter housing
BK 04	35	87,5	35	20	S040
BK 05	35	117,5	65	38	S050
BK 06	35	172,5	100	58,8	S055
BK 07	48	175	150	88	S075
BK 10	48	242,5	200	117,7	M010
BK 12	48	277	250	147	M012
BK 15	83	213,5	320	188	M015
BK 18	83	266,5	420	247	M018
BK 20	83	316,5	600	353	M020
BK 22	83	413	780	459	M022
BK 23	83	531	1020	600	M023
BK 25	129	411,5	1300	765	M025
BK 27	129	515,5	1620	953	M027
BK 30	129	636	1940	1142	M030
BK 32	129	783	2400	1412	M032
BK 88	82	789	1580	930	L080-L304

\*Filter cartridge names consist of cartridge size and filtration grade. Place filtration grade designation after filter size (e.g. BK 04 G).

## MAINTENANCE

G, F, S - Replace filter element at least once per year or when pressure drop reaches 350mbar

A - Replace filter element at least every 6 months



## Strength

- We export to almost 100 countries.
- We have more than 2000 global customers.
- We can provide a total filtration solution.

- Filter-Online & Nordic Filtration offers a wide selection of filtration products for Domestic and Industrial Application.

- You can buy our products on our websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our websites:

[www.filter-online.com](http://www.filter-online.com) for Domestic Products

[nordicfiltration.com](http://nordicfiltration.com) for Industrial Products

We distribute many of our products from our stock in Denmark. Some products are shipped from remote stock.



Filter-Online & Nordic Filtration ApS  
Glasvænget 6  
5492 Vissenbjerg  
Denmark

**Filter-Online**  
+45 70 40 42 22  
[info@filter-online.com](mailto:info@filter-online.com)  
[www.filter-online.com](http://www.filter-online.com)

**Nordic Filtration**  
+45 72 25 10 00  
[info@nordicfiltration.com](mailto:info@nordicfiltration.com)  
[nordicfiltration.com](http://nordicfiltration.com)