

# FILTER ELEMENT – Worthington

Alternative filter elements for Worthington Creysensac  
Series: Multibrand Old

## DESCRIPTION

These filter elements have been developed for high efficient removal of solid particles, oil aerosols, water, hydrocarbons, vapours and odours from compressed air.



## FILTER ELEMENT RATING ACCORDING TO ISO 8573-1

Filtration grade	Solid particles class	Water class	Oil class
P	6	/	/
D	2	/	2
M	1	/	1
A	1*	/	0/1

Validated according to ISO12500-1, ISO12500-2 and ISO12500-3

## TECHNICAL SPECIFICATION

	P	D	M	A
Operating temperature	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 45 °C/ 35 - 113 °F
Operating pressure	0 - 16 barg/ 0 - 232 psi			
Differential pressure (dry)	10 mbar/ 0,145 psi	50 mbar/ 0,725 psi	80 mbar/ 1,160 psi	60 mbar/ 0,870 psi
Differential pressure (wet)	20 mbar/ 0,290 psi	120 mbar/ 1,740 psi	190 mbar/ 2,756 psi	/
Particle retention (nominal)	99,99% (3 µm)	99,9999% (0,1 µm)	99,9999% (0,01 µm)	/
Particle retention rate ISO <sup>(3)</sup>	95 %	99,98 %	99,998 %	/
Residual oil content <sup>(4)</sup>	/	< 0,1mg/m <sup>3</sup>	< 0,01mg/m <sup>3</sup>	< 0,005mg/m <sup>3</sup>
Flow Direction	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE
Capacity (ISO12500-2) <sup>(5)</sup>	/	/	/	20 min

Tested according to ISO12500-3, 1bar(a), nominal flow, 06050 P, MPPS-(5µm) ; 06050 M, S, MPPS-(0,3µm)

Tested according to ISO12500-1, 06050 M, S Oil aerosol viscosity 32mm<sup>2</sup>/s, inlet concentration 10mg/m<sup>3</sup>

Tested according to ISO12500-2, 06050 A, tested with n-Hexane, test concentration 100mg/kg, 80% Saturation

## CORRECTION FACTORS

To calculate the correct capacity of a given filter based on actual operating conditions, multiply the nominal flow capacity by the appropriate correction factor(s). CORRECTED CAPACITY = NOMINAL FLOW CAPACITY x C<sub>OP</sub>

### OPERATING PRESSURE

[bar]	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
[psi]	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232
C <sub>OP</sub>	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13

## MATERIALS

	P	D	M	A
Filter media	Acrylic fibers, cellulose	Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers
Protection media	Polyester fleece	Polyester fleece	Polyester fleece	Polyester fleece
Drainage media	/	Polyester needle felt	Polyester needle felt	/
Adsorption media	/	/	/	Activated carbon granulate
Support (inner-outer)	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301
Bonding	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Endcaps	PA6 with 30% glass fibers			
Sealing	NBR	NBR	NBR	NBR

## SIZES

Model*	Diameter [mm]	Height [mm]	Flow Capacity [Nm <sup>3</sup> /h]	Flow Capacity [scfm]	Fits into filter housing
60	51	60	60	35	60
80	51	70	78	46	80
120	51	140	120	71	120
200	75	125	198	117	200
340	75	225	335	197	340
510	75	325	510	300	510
800	75	505	780	459	800
1000	90	510	996	586	1000
1500	90	760	1500	883	1500
2400	140	750	2400	1413	2400

\*Filter cartridge names consist of cartridge size and filtration grade. Place filtration grade designation after filter size (e.g. 60 P).

## MAINTENANCE

P, D, M - Replace filter element at least once per year or when pressure drop reaches 350mbar

A - Replace filter element at least every 6 months



## Strength

- We export to almost 100 countries.
- We have more than 2000 global customers.
- We can provide a total filtration solution.

- Filter-Online & Nordic Filtration offers a wide selection of filtration products for Domestic and Industrial Application.

- You can buy our products on our websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our websites:

[www.filter-online.com](http://www.filter-online.com) for Domestic Products

[nordicfiltration.com](http://nordicfiltration.com) for Industrial Products

We distribute many of our products from our stock in Denmark. Some products are shipped from remote stock.



Filter-Online & Nordic Filtration ApS  
Glasvænget 6  
5492 Vissenbjerg  
Denmark

**Filter-Online**  
+45 70 40 42 22  
[info@filter-online.com](mailto:info@filter-online.com)  
[www.filter-online.com](http://www.filter-online.com)

**Nordic Filtration**  
+45 72 25 10 00  
[info@nordicfiltration.com](mailto:info@nordicfiltration.com)  
[nordicfiltration.com](http://nordicfiltration.com)