

AxSorb D 2 - 5

Technical Data Sheet



Application: Highly recommended for air and gas drying, where high water adsorption capacity combined with excellent mechanical properties are mandatory.

Description: Regenerative Activated Alumina with high water adsorption capacity and strong attrition resistance to ensure less dust formation to protect downstream valves and minimize filter plugging.

AxSorb D presents an exceptional cyclic stability in Thermal Swing Adsorption (TSA) applications as it minimizes hydrothermal ageing when meeting low dew point specifications. It also shows long term performance in Pressure Swing Adsorption (PSA) applications because of its very good mechanical properties.

TYPICAL PROPERTIES		
High purity Alumina beads		
Diameter	2.0 to 5.0	mm
Alumina (Al ₂ O ₃)	93.5 min.	wt%
Sodium oxide (Na ₂ O)	3200	wt ppm
Loss on ignition (300-1000°C)	5	wt%
Surface area	335	m ² /g
Total pore volume	44	cm ³ /100g
Sock loading density	780	kg/m ³
Dense loading density	860	kg/m ³
Particle crushing strength	19	daN
Attrition resistance (AIF method)	99.5	wt%
Statistic adsorption (at 60% RH)	21.5	wt%

These indicative properties do not represent process capabilities nor specifications.

SHIPPING INFORMATION	
Packaging	217 l. fiber drums. Net 160 kg (353 lbs)

Nordic Filtration

At www.nordicfiltration.com you will find a wide selection of filtration products ready for you to order.

Nordic Filtration offers a wide selection of filtration products for water treatment. We have stock in Denmark from where we distribute all of our products to Scandinavia and the the rest of the world.

You can buy our products on local websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our website (www.nordicfiltration.com).

We can adapt all of our filtration products to your needs, and we offer visits from our consultants in order to find the right solution for you.

