

## DSI Refrigeration Dryers



### Specifications

Ambient temp. °C:	25
inlet air pressure, bar:	7
dew point:	class 5 (ISO 8573-1)

DSI refrigerated air dryers are available in operating 7 bar. Unique heat exchanger, heavy duty construction, reliable and long lasting. The series have the advantages of size reducing and anti-corrosion.

Data						
Model	Refrigerant	m3/h	Connection (BSP-F)	Dimensions WxLxH(mm)	Weight	Power Supply
DSI-30	R134a	30	3/4"	305x373x440	18	230/1/50hz
DSI-42	R134a	42	3/4"	305x373x440	18	230/1/50hz
DSI-60	R134a	60	3/4"	305x373x440	19	230/1/50hz
DSI-90	R134a	90	3/4"	345x409x480	21	230/1/50hz
DSI-120	R134a	120	3/4"	345x409x480	24	230/1/50hz
DSI-150	R134a	150	1"	396x462x536	27	230/1/50hz
DSI-192	R134a	192	1"	396x462x536	35	230/1/50hz
DSI-240	R134a	240	1"	396x462x536	41	230/1/50hz
DSI-330	R407C	330	1 1/2"	538x538x684	55	230/1/50hz
DSI-366	R407C	366	1 1/2"	527x627x1123	72	230/1/50hz
DSI-440	R407C	440	1 1/2"	527x627x1123	72	230/1/50hz
DSI-560	R407C	560	1 1/2"	527x627x1123	78	230/1/50hz
From DSI 150, optional converter TTLK/RS485 • Request for 60hz version						