

# FILTER ELEMENT – WALKER

## Alternative filter elements for Walker

### DESCRIPTION

These filter elements have been developed for high efficient removal of solid particles, oil aerosols, water, hydrocarbons, vapours and odours from compressed air.

### FILTER ELEMENT RATING ACCORDING TO ISO 8573-1



Filtration grade	Solid particles class	Water class	Oil class
X5	6	/	/
X1	2	/	2
XA	1	/	1
AC	1*	/	0/1

Validated according to ISO12500-1, ISO12500-2 and ISO12500-3

\* Valid if "XS" filter cartridge is installed upstream

### TECHNICAL SPECIFICATION

	X5	X1	XA	AC
Operating temperature	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 45 °C/ 35 - 113 °F
Operating pressure	0 - 16 barg/ 0 - 232 psi			
Differential pressure (dry)	10 mbar/ 0,145 psi	50 mbar/ 0,725 psi	80 mbar/ 1,160 psi	60 mbar/ 0,870 psi
Differential pressure (wet)	20 mbar/ 0,290 psi	120 mbar/ 1,740 psi	190 mbar/ 2,756 psi	/
Particle retention (nominal)	99,99% (3 µm)	99,9999% (0,1 µm)	99,9999% (0,01 µm)	/
Particle retention rate ISO <sup>(3)</sup>	95 %	99,98 %	99,9994 %	/
Residual oil content <sup>(4)</sup>	/	< 0,1mg/m <sup>3</sup>	< 0,01mg/m <sup>3</sup>	< 0,005mg/m <sup>3</sup>
Flow Direction	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE
Capacity (ISO12500-2) <sup>(5)</sup>	/	/	/	20 min

<sup>(3)</sup>Tested according to ISO12500-3, 1bar(a), nominal flow, 06050 P, MPPS-(5µm) ; 06050 M, S, MPPS-(0,3µm)

<sup>(4)</sup>Tested according to ISO12500-1, 06050 M, S Oil aerosol viscosity 32mm<sup>2</sup>/s, inlet concentration 10mg/m<sup>3</sup>

<sup>(5)</sup>Tested according to ISO12500-2, 06050 A, tested with n-Hexane, test concentration 100mg/kg, 80% Saturation

### CORRECTION FACTORS

To calculate the correct capacity of a given filter based on actual operating conditions, multiply the nominal flow capacity by the appropriate correction factor(s).

$$\text{CORRECTED CAPACITY} = \text{NOMINAL FLOW CAPACITY} \times C_{OP}$$

### OPERATING PRESSURE

[bar]	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
[psi]	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232
C <sub>OP</sub>	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13

## MATERIALS

	X5	X1	XA	AC
Filter media	Acrylic fibers, cellulose	Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers
Protection media	Polyester fleece	Polyester fleece	Polyester fleece	Polyester fleece
Drainage media	/	Polyester needle felt	Polyester needle felt	/
Adsorption media	/	/	/	Activated carbon granulate
Support (inner-outer)	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301
Bonding	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Endcaps	Aluminium	Aluminium	Aluminium	Aluminium
Sealing	NBR	NBR	NBR	NBR

## SIZES

Model	Diameter [mm]	Height [mm]	Flow Capacity [Nm <sup>3</sup> /h]	Flow Capacity [scfm]	Fits into filter housing
E361	43	73	35	20	A20
E371	43	73	56	33	A30
E381	38	117	25; 50	15; 30	D20/D30
E511	54,5	113	112	66	A55
E711	72	150	216	127	A76
E811	83	149	250	147	A105
E731	72	300	300	176	A106
E821	83	300	540	318	A126
E831	83	301	725; 800	427; 470	A153/A203
E851	83	500	1150	675	A205
E1251	130	497	1620	954	A250/A305
E1261	130	615	2210	1301	A306
E1281	130	763	2600	1531	A308
E139	130	766	2160	1270	A391
E88	83	790	3100	1824	A483
			4250	2500	A484
			6500	3824	A686
			8720	5130	A688
			11000	6470	A8810
			17000	10000	A10816
			25000	15000	A12824

\*Filter cartridge names consist of cartridge size and filtration grade. Place filtration grade designation after filter size (e.g. OWA E361 X5/P AI).

## MAINTENANCE

X5, X1, XA - Replace filter element at least once per year or when pressure drop reaches 350mbar

AC- Replace filter element at least every 6 months



## Strength

- We export to almost 100 countries.
- We have more than 2000 global customers.
- We can provide a total filtration solution.

- Filter-Online & Nordic Filtration offers a wide selection of filtration products for Domestic and Industrial Application.

- You can buy our products on our websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our websites:

[www.filter-online.com](http://www.filter-online.com) for Domestic Products

[nordicfiltration.com](http://nordicfiltration.com) for Industrial Products

We distribute many of our products from our stock in Denmark. Some products are shipped from remote stock.



Filter-Online & Nordic Filtration ApS  
Glasvænget 6  
5492 Vissenbjerg  
Denmark

**Filter-Online**  
+45 70 40 42 22  
[info@filter-online.com](mailto:info@filter-online.com)  
[www.filter-online.com](http://www.filter-online.com)

**Nordic Filtration**  
+45 72 25 10 00  
[info@nordicfiltration.com](mailto:info@nordicfiltration.com)  
[nordicfiltration.com](http://nordicfiltration.com)