

Atlas Copco - Datasheet



Specifications

Size, "(inch):	see table
Particle Retention rating, µm:	0,01 - 3
Flow capacity, nm3/h:	35 - 1100
Op. Temp. C°:	1,5 - 65
Diff. Pressure:	10 - 60(dry) - 20 - 190(wet)
Efficiency, % (nominal):	99,99 - 99,9999
Connection:	-
Material:	-
Sealing:	NBR

These filter elements have been developed for high efficient removal of solid particles, oil aerosols, water, hydrocarbons, vapours and odours from compressed air.

Filter element rating (ISO 8573-1)

Filtration grade	Solid particle class	Water class	Oil class
DD/DDP	2	/	2
PD	1	/	1
QD	1*	/	0/1

Technical Specifications

	DD/DDP	PD	QD
Operating temp.	1,5-65°C	1,5-65°C	1,5-45°C
Operating pressure	0-16 barg	0-16 barg	0-16 barg
Differential pressure (dry)	50 mbar	80 mbar	60 mbar
Differential pressure (wet)	120 mbar	190 mbar	-
Particle retention (nominal)	99,9999% (0,1µm)	99,9999% (0,01µm)	-
Particle retention rate ISO(3)	99,98%	99,9994%	-
Residual oil content(4)	<0,1mg/m3	<0,01mg/m3	<0,005mg/m3
Flow Direction	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE
Capacity (ISO12500-2)(5)	-	-	20 min

3* Tested according to ISO12500-3, 1bar(a), nominal flow, 0605 P, MPPS-(5µm) ; 06050 R, M, S, MPPS-(0,3µm)

4* Tested according to ISO12500-1, 06050 M, S Oil aerosol viscosity 32 mm2/s, inlet concentration 10 mf/m3

5* Tested according to ISO12500-2, 06050 A, tested with n-Hexane, test concentration 100mg/kg, 80% Saturation

Correction factors															
Operating pressure															
bar	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
C _{op}	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13

Materials					
			DD/DDP	PD	QD
Filter media			Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers
Protection media			Polyester fleece	Polyester fleece	Polyester fleece
Drainage media			Polyester needle felt	Polyester needle felt	-
Adsorption media			-	-	Activated carbon granulate
Support (inner-outer)			Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301
Bonding			Polyurethane	Polyurethane	Polyurethane
Endcaps			PA6 with 30% glass fibers	PA6 with 30% glass fibers	PA6 with 30% glass fibers
Sealing			NBR	NBR	NBR

* filter cartridge names consists of cartridge size and filtration grade. Place filtration grade designation after filter size.

MAINTENANCE

P/P, V/XR, M/XM, S/XS - Replace filter element at least once per year or when pressure drop reaches 350mbar

A/A - Replace filter element at least every 6 months