

FILTER ELEMENT – BEA

Alternative filter elements for BEA technologies

Series: ARS (Air Vip)

DESCRIPTION

Bea ARS filter elements have been developed for high efficient removal of solid particles, oil aerosols, water, hydrocarbons, vapours and odours from compressed air.



FILTER ELEMENT RATING ACCORDING TO ISO 8573-1

Filtration grade	Solid particles class	Water class	Oil class
RM	6	/	/
RF	3	/	/
RB	2	/	2
RA	1	/	1
CA	1*	/	0/1

Validated according to ISO12500-1, ISO12500-2 and ISO12500-3

TECHNICAL SPECIFICATION

	RM	RF	RB	RA	CA
Operating temperature	1,5 - 65 °C/ 35 - 149 °F	1,5 - 45 °C/ 35 - 113 °F			
Operating pressure	0 - 16 barg/ 0 - 232 psi				
Differential pressure (dry)	10 mbar/ 0,145 psi	20 mbar/ 0,290 psi	50 mbar/ 0,725 psi	80 mbar/ 1,160 psi	60 mbar/ 0,870 psi
Differential pressure (wet)	20 mbar/ 0,290 psi	40 mbar/ 0,580 psi	120 mbar/ 1,740 psi	190 mbar/ 2,756 psi	/
Particle retention (nominal)	99,99% (3 µm)	99,9999% (1 µm)	99,9999% (0,1 µm)	99,9999% (0,01 µm)	/
Particle retention rate ISO ⁽³⁾	95 %	99,8 %	99,98 %	99,9994 %	/
Residual oil content ⁽⁴⁾	/	/	< 0,1mg/m ³	< 0,01mg/m ³	< 0,005mg/m ³
Flow Direction	INSIDE to OUTSIDE				
Capacity (ISO12500-2) ⁽⁵⁾	/	/	/	/	20 min

⁽³⁾Tested according to ISO12500-3, 1bar(a), nominal flow, 06050 P, MPPS-(5µm) ; 06050 R, M, S, MPPS-(0,3µm)

⁽⁴⁾Tested according to ISO12500-1, 06050 M, S Oil aerosol viscosity 32mm²/s, inlet concentration 10mg/m³

⁽⁵⁾Tested according to ISO12500-2, 06050 A, tested with n-Hexane, test concentration 100mg/kg, 80% Saturation

CORRECTION FACTORS

To calculate the correct capacity of a given filter based on actual operating conditions, multiply the nominal flow capacity by the appropriate correction factor(s). CORRECTED CAPACITY = NOMINAL FLOW CAPACITY x C_{OP}

OPERATING PRESSURE

[bar]	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
[psi]	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232
C _{OP}	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13

MATERIALS

	RM	RF	RB	RA	CA
Filter media	Acrylic fibers, cellulose	Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers
Protection media	Polyester fleece				
Drainage media	/	Polyester needle felt	Polyester needle felt	Polyester needle felt	/
Adsorption media	/	/	/	/	Activated carbon granulate
Support (inner-outer)	Stainless steel 1.4301				
Bonding	Polyurethane	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Endcaps	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Sealing	NBR	NBR	NBR	NBR	NBR

SIZES

Model*	Diameter [mm]	Height [mm]	Flow Capacity [Nm ³ /h]	Flow Capacity [scfm]	Fits into filter housing
BE ARS 30	45	60	30	18	CDF-30
BE ARS 100	45	150	60 100	35 59	CDF-60 CDF-100
BE ARS 180	59	150	180	106	CDF-180
BE ARS 290	59	250	290	171	CDF-290
BE ARS 460	71,5	250	460	271	CDF-460
BE ARS 610	71,5	350	610	359	CDF-610
BE ARS 930	81,5	373	930	547	CDF-930
BE ARS 1050	81,5	473	1050	618	CDF-1050
BE ARS 1400	120	344	1500 2200	883 1295	CDF-1500 CDF-2200/ACF
BE ARS 2300	81,5	473	2300	1354	CDF-2300

*Filter cartridge names consist of cartridge size and filtration grade. Place filtration grade designation after filter size (e.g. BE ARS 30 RM AI).

MAINTENANCE

RM, RF, RB, RA - Replace filter element at least once per year or when pressure drop reaches 350mbar CA - Replace filter element at least every 6 months



Strength

- We export to almost 100 countries.
- We have more than 2000 global customers.
- We can provide a total filtration solution.

- Filter-Online & Nordic Filtration offers a wide selection of filtration products for Domestic and Industrial Application.

- You can buy our products on our websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our websites:

www.filter-online.com for Domestic Products

nordicfiltration.com for Industrial Products

We distribute many of our products from our stock in Denmark. Some products are shipped from remote stock.



Filter-Online & Nordic Filtration ApS
Glasvænget 6
5492 Vissenbjerg
Denmark

Filter-Online
+45 70 40 42 22
info@filter-online.com
www.filter-online.com

Nordic Filtration
+45 72 25 10 00
info@nordicfiltration.com
nordicfiltration.com