



FILTER ELEMENT – ABAC F

Alternative filter elements for Abac

Series: Multibrand F

DESCRIPTION

ABAC F filter elements have been developed for high efficient removal of solid particles, oil aerosols, water, hydrocarbons, vapours and odours from compressed air.



FILTER ELEMENT RATING ACCORDING TO ISO 8573-1

Filtration grade	Solid particles class	Water class	Oil class
P	3	/	3
G-S	2	/	2
C-D	1	/	1
V	1*	/	0/1

Validated according to ISO12500-1, ISO12500-2 and ISO12500-3

TECHNICAL SPECIFICATION

	P	G-S	C-D	V
Operating temperature	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 65 °C/ 35 - 149 °F	1,5 - 45 °C/ 35 - 113 °F
Operating pressure	0 - 20 barg/ 0 - 290 psi	0 - 20 barg/ 0 - 290 psi	0 - 20 barg/ 0 - 290 psi	0 - 20 barg/ 0 - 290 psi
Differential pressure (dry)	20 mbar/ 0,290 psi	50 mbar/ 0,725 psi	80 mbar/ 1,160 psi	60 mbar/ 0,870 psi
Differential pressure (wet)	40 mbar/ 0,580 psi	120 mbar/ 1,740 psi	190 mbar/ 2,756 psi	/
Particle retention (nominal)	99,9999% (1 µm)	99,9999% (0,1 µm)	99,9999% (0,01 µm)	/
Particle retention rate ISO ⁽³⁾	99,8 %	99,98 %	99,998 %	/
Residual oil content ⁽⁴⁾	/	< 0,1mg/m ³	< 0,01mg/m ³	< 0,005mg/m ³
Flow Direction	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE	INSIDE to OUTSIDE
Capacity (ISO12500-2) ⁽⁵⁾	/	/	/	20 min

⁽³⁾Tested according to ISO12500-3, 1bar(a), nominal flow, 06050 R, M, S, MPPS-(0,3µm)

⁽⁴⁾Tested according to ISO12500-1, 06050 M, S Oil aerosol viscosity 32mm²/s, inlet concentration 10mg/m³

⁽⁵⁾Tested according to ISO12500-2, 06050 A, tested with n-Hexane, test concentration 100mg/kg, 80% Saturation

CORRECTION FACTORS

To calculate the correct capacity of a given filter based on actual operating conditions, multiply the nominal flow capacity by the appropriate correction factor(s). CORRECTED CAPACITY = NOMINAL FLOW CAPACITY x C_{OP}

OPERATING PRESSURE

[bar]	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
[psi]	29	44	58	72	87	100	115	130	145	160	174	189	203	218	232	247	261	276	290
C _{OP}	0,38	0,5	0,63	0,75	0,88	1	1,13	1,25	1,38	1,50	1,63	1,75	1,88	2,00	2,13	2,25	2,38	2,50	2,63



MATERIALS

	P/XR	G-S/XM	C-D/XS	V/A
Filter media	Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers	Borosilicate micro fibers
Protection media	Polyester fleece	Polyester fleece	Polyester fleece	Polyester fleece
Drainage media	Polyester needle felt	Polyester needle felt	Polyester needle felt	/
Adsorption media	/	/	/	Activated carbon granulate
Support (inner-outer)	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301	Stainless steel 1.4301
Bonding	Polyurethane	Polyurethane	Polyurethane	Polyurethane
Endcaps	PA6 with 30% glass fibers	PA6 with 30% glass fibers	PA6 with 30% glass fibers	PA6 with 30% glass fibers
Sealing	NBR	NBR	NBR	NBR

SIZES

Model*	Diameter [mm]	Height [mm]	Flow Capacity [Nm ³ /h]	Flow Capacity [scfm]	Fits into filter housing
AB F1	28	59,5	10	6	F_ - 1 F_ 10 (G1/8) - AB
AB F2	28	59,5	25	15	F_ - 2 F_ 25 (G1/4) - AB
AB F3	38,5	80,5	42	25	F_ - 3 F_ 42 (G1/4) - AB
AB F4	38,5	80,5	54	32	F_ - 4 F_ 54 (G3/8) - AB
AB F5	38,5	123	85	50	F_ - 5 F_ 85 (G1/2) - AB
AB F6	65	120,5	119	70	F_ - 6 F_ 119 (G1/2) - AB
AB F7	65	120,5	144	85	F_ - 7 F_ 144 (G3/4) - AB
AB F8	65	120,5	178	105	F_ - 8 F_ 178 (G1) - AB
AB F9	65	205,5	212	125	F_ - 9 F_ 212 (G3/4) - AB
AB F10	65	205,5	297	175	F_ - 10 F_ 297 (G1) - AB
AB F11	72	305	476	280	F_ - 11 F_ 476 (G1 1/4) - AB
AB F12	72	305	545	321	F_ - 12 F_ 545 (G1 1/2) - AB
AB F13	83	307	765	450	F_ - 13 F_ 765 (G2) - AB
AB F14	83	509	1189	700	F_ - 14 F_ 1189 (G2) - AB
AB F15	130	497	1444	850	F_ - 15 F_ 1444 (G2 1/2) - AB
AB F16	130	497	1529	900	F_ - 16 F_ 1529 (G3) - AB
AB F17	130	619	2125	1250	F_ - 17 F_ 2125 (G3) - AB
AB F18	130	769	2550	1500	F_ - 18 F_ 2550 (G3) - AB

*Filter cartridge names consist of cartridge size and filtration grade. Place filtration grade designation after filter size (e.g. AB F1 P).

MAINTENANCE

P, G-S, C-D - Replace filter element at least once per year or when pressure drop reaches 350mbar

V - Replace filter element at least every 6 months



Strength

- We export to almost 100 countries.
- We have more than 2000 global customers.
- We can provide a total filtration solution.

- Filter-Online & Nordic Filtration offers a wide selection of filtration products for Domestic and Industrial Application.

- You can buy our products on our websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our websites:

www.filter-online.com for Domestic Products

nordicfiltration.com for Industrial Products

We distribute many of our products from our stock in Denmark.
Some products are shipped from remote stock.



Filter-Online & Nordic Filtration ApS
Glasvænget 6
5492 Vissenbjerg
Denmark

Filter-Online
+45 70 40 42 22
info@filter-online.com
www.filter-online.com

Nordic Filtration
+45 72 25 10 00
info@nordicfiltration.com
nordicfiltration.com