

FILTER ELEMENT - AFE

Alternative filter elements for Airfilter Engineering

Series: G-series



DESCRIPTION

AFE filter elements have been developed for high efficient removal of solid particles, oil aerosols, water, hydrocarbons, vapours and odours from compressed air.

FILTER ELEMENT RATING ACCORDING TO ISO 8573-1

| Filtration grade | Solid particles class | Water class | Oil class |
|------------------|-----------------------|-------------|-----------|
| P | 6 | / | / |
| U | 3 | / | / |
| H | 2 | / | 2 |
| S | 1 | / | 1 |
| C | 1* | / | 0/1 |

Validated according to ISO12500-1, ISO12500-2 and ISO12500-3

TECHNICAL SPECIFICATION

| | P | U | H | S | C |
|--|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|
| Operating temperature | 1,5 - 65 °C/ 35 - 149 °F | 1,5 - 45 °C/ 35 - 113 °F |
| Operating pressure | 0 - 16 barg/ 0 - 232 psi |
| Differential pressure (dry) | 10 mbar/ 0,145 psi | 20 mbar/ 0,290 psi | 50 mbar/ 0,725 psi | 80 mbar/ 1,160 psi | 60 mbar/ 0,870 psi |
| Differential pressure (wet) | 20 mbar/ 0,290 psi | 40 mbar/ 0,580 psi | 120 mbar/ 1,740 psi | 190 mbar/ 2,756 psi | / |
| Particle retention (nominal) | 99,99% (3 µm) | 99,9999% (1 µm) | 99,9999% (0,1 µm) | 99,9999% (0,01 µm) | / |
| Particle retention rate ISO ⁽³⁾ | 95 % | 99,8 % | 99,98 % | 99,9994 % | / |
| Residual oil content ⁽⁴⁾ | / | / | < 0,1mg/m ³ | < 0,01mg/m ³ | < 0,005mg/m ³ |
| Flow Direction | INSIDE to OUTSIDE |
| Capacity (ISO12500-2) ⁽⁵⁾ | / | / | / | / | 20 min |

(3) Tested according to ISO12500-3, 1bar(a), nominal flow, 06050 P, MPPS-(5µm) ; 06050 R, M, S, MPPS-(0,3µm)

(4) Tested according to ISO12500-1, 06050 M, S Oil aerosol viscosity 32mm²/s, inlet concentration 10mg/m³

(5) Tested according to ISO12500-2, 06050 A, tested with n-Hexane, test concentration 100mg/kg, 80% Saturation

CORRECTION FACTORS

To calculate the correct capacity of a given filter based on actual operating conditions, multiply the nominal flow capacity by the appropriate correction factor(s). CORRECTED CAPACITY = NOMINAL FLOW CAPACITY x C_{OP}

OPERATING PRESSURE

| | | | | | | | | | | | | | | | |
|-----------------|------|-----|------|------|------|-----|------|------|------|------|------|------|------|------|------|
| [bar] | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
| [psi] | 29 | 44 | 58 | 72 | 87 | 100 | 115 | 130 | 145 | 160 | 174 | 189 | 203 | 218 | 232 |
| C _{OP} | 0,38 | 0,5 | 0,63 | 0,75 | 0,88 | 1 | 1,13 | 1,25 | 1,38 | 1,50 | 1,63 | 1,75 | 1,88 | 2,00 | 2,13 |

MATERIALS

| | P | U | H | S | C |
|-----------------------|---|---|---|---|---|
| Filter media | Acrylic fibers, cellulose | Borosilicate micro fibers | Borosilicate micro fibers | Borosilicate micro fibers | Borosilicate micro fibers |
| Protection media | Polyester fleece |
| Drainage media | / | Polyester needle felt | Polyester needle felt | Polyester needle felt | / |
| Adsorption media | / | / | / | / | Activated carbon granulate |
| Support (inner-outer) | Stainless steel 1.4301 |
| Bonding | Polyurethane PA6 with 30% glass fibers or aluminium | Polyurethane PA6 with 30% glass fibers or aluminium | Polyurethane PA6 with 30% glass fibers or aluminium | Polyurethane PA6 with 30% glass fibers or aluminium | Polyurethane PA6 with 30% glass fibers or aluminium |
| Endcaps | | | | | |
| Sealing | NBR | NBR | NBR | NBR | NBR |

SIZES

| Model* | Diameter [mm] | Height [mm] | Flow Capacity [Nm ³ /h] | Flow Capacity [scfm] | Fits into filter housing |
|-----------|---------------|-------------|------------------------------------|----------------------|--------------------------|
| AFE EA10 | 51 | 52 | 30 | 18 | G0010 |
| AFE EA15 | 51 | 59 | 50 | 29 | G0015 |
| AFE EA20 | 51 | 75 | 70 | 41 | G0020 |
| AFE EA30 | 51 | 144 | 100 | 59 | G0030 |
| AFE EA55 | 75 | 118 | 180 | 106 | G0055 |
| AFE EA95 | 75 | 218 | 300 | 177 | G0095 |
| AFE EA150 | 75 | 318 | 470 | 277 | G0150 |
| AFE EA220 | 75 | 508 | 700 | 412 | G0220 |
| AFE EA290 | 92 | 506 | 940 | 553 | G0290 |
| AFE EA430 | 92 | 760 | 1450 | 853 | G0430 |
| AFE EA625 | 140 | 605 | 1940 | 1142 | G0625 |
| AFE EA775 | 140 | 755 | 2400 | 1413 | G0775 |

*Filter cartridge names consist of cartridge size and filtration grade. Place filtration grade designation after filter size (e.g. AFE EA10 P). There is an option for **aluminum endcaps** (e.g. OAFE EA10 P Al).

MAINTENANCE

P, U, H, S - Replace filter element at least once per year or when pressure drop reaches 350mbar

C- Replace filter element at least every 6 months



Strength

- We export to almost 100 countries.
- We have more than 2000 global customers.
- We can provide a total filtration solution.

- Filter-Online & Nordic Filtration offers a wide selection of filtration products for Domestic and Industrial Application.

- You can buy our products on our websites or by contacting us by phone or e-mail. Information about our products as well as brochures and manuals can be found on our websites:

www.filter-online.com for Domestic Products

nordicfiltration.com for Industrial Products

We distribute many of our products from our stock in Denmark. Some products are shipped from remote stock.



Filter-Online & Nordic Filtration ApS
Glasvænget 6
5492 Vissenbjerg
Denmark

Filter-Online
+45 70 40 42 22
info@filter-online.com
www.filter-online.com

Nordic Filtration
+45 72 25 10 00
info@nordicfiltration.com
nordicfiltration.com